

Linkcrypt – Check status

1.1. Parameter:

Request Method: GET/POST

API-Link: <http://linkcrypt.ws/api.html>

field names are Case-Sensitiv

Benötigte Felder:

field names	description	example value
api	Choose API. Send always status_V1!	status_V1
folderKey	The folder ID	yw923tt7h875489

Optionale Felder:

fieldnames	description	Beispielwert
detail	Returns detailed information about the folder (no example available)	1 = Enabled 0 = Disabled Default: 0

1.2. Return values:

The API returns XML.

On success:

```
<?xml version="1.0"?>
<data>
  <status>1</status>
  <folderKey>[FOLDERKEY]</folderKey>
  <folderStatus>[FOLDERSTATUS]</folderStatus>
  <folderSize>[FOLDERSIZE]</folderSize>
  <folderHoster>[FOLDERHOSTER]</folderHoster>
</data>
```

[FOLDERKEY] = Folder ID

[FOLDERSTATUS] = Folder status (0=Unchecked,1=Online,2=Offline,3=Mixed,4=Plugin-out of order)

[FOLDERSIZE] = Size in MB

[FOLDERHOSTER] = Hoster separated by semicolons

Example:

```
<?xml version="1.0"?>
<data>
  <status>1</status>
  <folderKey>yw923tt7h875489</folderKey>
  <folderStatus>1</folderStatus>
  <folderSize>0</folderSize>
  <folderHoster>google.de</folderHoster>
</data>
```

On Error:

```
<?xml version="1.0"?>
<data>
  <status>0</status>
  <errorCode>[ERRORCODE]</folderKey>
  <errorMsg>[ERRORMSG]</errorMsg>
</data>
```

[ERRORCODE] = Error code
[ERRORMSG] = Error message

Example:

```
<?xml version="1.0"?>
<data>
  <status>0</status>
  <errorCode>1101</folderKey>
  <errorMsg>ERROR: Folder not Found</errorMsg>
</data>
```

Possible errors:

Error code	Error message	Description
1000	ERROR: Not API Selected	You have selected an invalid API. Check whether you send status_V1
1101	ERROR: Folder not Found	Folder could not be found